



Smart Wall Switch(L&N)




Parameter


Power Parameter:	100-240V AC, 50/60Hz
Standby Power Consumption:	≤0.5W
Total Maximum Resistance Load: Incandescent Lamp:	100V~: Max.1000W/10A 240V~: Max.2400W/10A
Total Maximum Inductive/Capacitive Load	100V~:Max 650W/6.5A
Energy Saving Lamp/Fluorescent Lamp/LED	240v~: Max 1560W/6.5A
Installation Method:	Wall-mounted Type
Working Temperature/Humidity:	-10°C~+45°C / ≤95%RH(noncondensing)
Material & Color:	PC, White
Dimensions (L*W*H):	86*87*40(mm)

Features

1. Communication Mode: IEEE 802.15.4 (ZigBee/SmartRoom).
2. Bidirectional feedback through App.
3. It can link with Smart IR Motion Detector, Smart Light Sensor to realize people come lights on; Link with light sensor to control N FF of lighting according to light intensity automatically; Convenient and energy saving.
4. Support time setting.
5. Scene editing, regional management, customize return-home and leave-home mode by a press.




Smart Switch (One-Gang, L&N)
WL-ZCSWNPW-S1311-04




Net Weight: 134g
Gross Weight: 320g

Smart Switch (Two-Gang, L&N)
WL-ZCSWNPW-S1321-04



Net Weight: 145g
Gross Weight: 300g

Smart Switch (Three-Gang, L&N)
WL-ZCSWNPW-S1331-04



Net Weight: 162g
Gross Weight: 351g